张家港市惠邦机械制造有限公司
ZHANGJIAGANG HUIBANG MACHINERY CO.,LTD

地　址: 江苏省张家港市常阴沙工业园
Add: Changyinsha Industrial Park, Zhangjiagang, Jiansu Province
电　话（TEL）: +86-512-58964890　+86-512-58639891
传　真（FAX）: +86-512-58964836
邮　箱（E-MAIL）: webmaster@hb1888.com
网　址（WEBSITE）: http://www.hb1888.com

Http://www.hb1888.com

惠邦机械
HUIBANG MACHINERY

张家港市惠邦机械制造有限公司
ZHANGJIAGANG HUIBANG MACHINERY CO.,LTD

公司简介 Company Profile

张家港市惠邦机械制造有限公司专业生产和出口塑料磨粉和挤出成型设备，集产品设计、研发和生产于一体。公司位于经济繁荣、风光旖旎的国际花园城市——江苏张家港。地处中国经济最为发达的长三角经济圈，紧临沪、宁、苏、锡、常等经济腹地，水陆空交通极为优越。

惠邦公司成立于 2006 年，是一家具有良好商誉和发展前景的企业，拥有占地 5000 平方米的现代化标准厂房及办公环境，经验丰富的技术人员和热情完善的服务团队。我们有信心有能力为客户提供高品质的塑料机械产品，同时，也可满足客户的差异化需求，提供更为专业的全套解决方案。我们主要产品有：塑料磨粉机、破碎机、撕碎机、混合机、单 / 双螺杆挤出机、塑料管材 / 型材（木塑）/ 板材 / 片材挤出生产线、牵引机、切割机、上料机、模温机等设备。产品以其优异的品质，出色的性价比，赢得了国内外客户的欢迎和好评！

我们秉持“为客户提供优质的产品和优良的服务”的宗旨，以高效、热情、诚信为标准，不仅注重产品质量，更力争为客户提供全程的完善的系统服务。

如果贵司对我们任一款产品感兴趣或有订单意向，欢迎随时联系我们。我们期待与全球客户携手合作，共创未来。

ZhangJiaGang Huibang Machinery Co., Ltd. is a professional manufacturer and exporter of plastic pulverizer and extrusion machinery. The corporation is located in Zhangjiagang, where is known as the international garden city and it got the Habitat Scroll of Honour Award in 2008. As a corporation in the Yangtze Delta Area, we enjoy the convenient transport system. Besides, we are not far from the important economic regions such as Shanghai, Ningbo, Suzhou, Wuxi and Changzhou.

Founded in 2006, Huibang machinery is a well-established corporation with good reputation and bright future. Now the corporation covers an area of 5000 square meters, including two modern factories and offices. We specialize in the production of plastic pulverizer, crusher, shredder, mixer, single and double screw extruder, plastic pipe/profile (wood & plastic)/ sheet/ plate extrusion line, haul-off, cutter, loader, mold temperature control and so on. What's more, the combination of first-class service and advanced technology ensures the fact that Huibang is the leading manufacturer in this line. Undoubtedly, Our products can satisfy any of your requirements. Due to the high quality and competitive price, our corporation has won the honour of Three A enterprise as well as the famous enterprise in Jiangsu province.

The pursuit of high quality products and excellent service always comes first. Last but not least, we'll strive for high efficiency, strong work ethic and good faith to provide customers with high-quality products.

If you are interested in any of our products, please feel free to contact us. We are looking forward to entering into business relations with you in the near future.

目录 Contents

MF系列新型立式磨盘磨粉机 05-06
MF SERIES DISC TYPE PLASTIC PULVERIZER
SMW系列静音型立式涡轮式塑料磨粉机 07-08
SMW SERIES MUTE VERTICAL TURBO-TYPE PLASTIC PULVERIZER
SMW系列高速涡轮式塑料磨粉机 09-10
SMW SERIES HIGH SPEED TURBO-TYPE PLASTIC PULVERIZER
SMW系列立式塑料磨粉机 11-12
SMW SERIES VERTICAL PLASTIC PULVERIZER
深冷粉碎机 13-14
CRYOGENIC MILL
PC系列塑料破碎机 15-16
PC SERIES CRUSHER
SWP系列塑料破碎机
SWP SERIES CRUSHER
单轴撕碎机 17-18
SS SERIES SHREDDER
SRL-W系列卧式混合机组 19-20
SRL-W SERIES HORIZONTAL TYPE MIXER
SRL-Z系列立式混合机组
SRL-Z SERIES VERTICAL TYPE MIXER
PE管材生产线 21-22
PE PIPE PRODUCTION LINE
UPVC双管挤出生产线
UPVC Double pipe Extrusion Line
PVC型材生产线 23-24
PVC PROFILES EXTRUSION LINE
宽幅门板生产线
PVC PLASTIC WOOD DOOR PANEL EXTRUDING PRODUCTION LINE
PE、PP薄膜破碎清洗线 25-26
PE、PP FILM CLEANING LINE
PET瓶片回收清洗设备(600-2000kg/h)
PET BOTTLE FLAKES RECYCLING, WASHING & CLEANING EQUIPMENT
辅助机械 27-28
AUXILIARY MACHINERY
我们的服务 29-30
OUR SERVICE

MF系列新型立式磨盘磨粉机

MF SERIES DISC TYPE PLASTIC PULVERIZER

MF系列新型立式磨盘磨粉机磨盘直径最小为350mm，最大为800mm，属于磨盘式磨粉机系列。广泛应用于硬度适中、耐冲击及易碎的物料，如PE、PVC、PP、ABS、PA、EVA、PET、PS、PPS、EPS、PC、泡沫、牛皮等等。

The brand-new MF series plastic pulverizer belongs to the Disc-type pulverizer series, with its disc diameter ranging from 350mm to 800mm.It is widely used in grinding materials that is of moderate hardness. For example PE，PVC，PP，ABS，PA，EVA，PET，PS，PPS，EPS，PC，Styrofoam，Cow leather and so on.

特点 Advantages

- 磨盘间隙调节安全可靠
- 低能耗，高产量
- 设计创新高效
- 操作维护简便
- 配套设施齐全
- 自动回磨功能
- 风水双冷却系统

- Safe and simple adjustment of cutting gap
- Low energy consumption and High throughput
- Innovative and energy efficient design
- Easy to maintain and control
- Wide range of accessories
- Regrinding coarse powder automatically
- Dual cooling system



主要技术参数 Main technical parameters

材料	Material	MF-400	MF-500	MF-600	MF-800
磨盘直径	Diameter (mm)	Φ400	Φ500	Φ600	Φ800
主电机功率	Main Motor (kw)	30	37	45	75
重量	Weight (kg)	1580	2280	2680	3280
外型尺寸	Dimensions(mm)	2800×2600×3700	3000×2800×3900	3200×3000×4200	4000×3500×4500
产量	Capacity(kg/h)	50-150	120-280	160-480	280-880

注：产量取决于磨粉材料的种类和磨粉细度，进料大小一般在5~8mm

Attention: the throughput depends on the types and size of grinding materials,along with the finess of the grinding materials.Usually, the original diameter of the material ranges from 5 to 8 mm.

应用 Applications

惠邦机械 MF 系列磨粉机最主要是应用于滚塑行业的 PE 粉体加工，为生产线提供 PE 粉料，通常配套使用振动筛以确保研磨 PE 粉料的细度精确，从而保证滚塑成型制品表面光滑，厚度均匀。同时也能与撕碎机、破碎机搭配，应用于常规塑料的回收领域。

One of the main fields that HUIBANG MF series plastic pulverizer applied to is the pulverization of PE. In this process, the vibration screen plays an important role in ensuring the accurate fineness of products. Morever, concomitant use with a shredder and crusher is firstly chosen in the field of recycling and reusing waste plastics.

SMW系列静音型立式涡轮式塑料磨粉机

SMW SERIES MUTE VERTICAL TURBO-TYPE PLASTIC PULVERIZER

SMW 系列静音型立式涡轮式塑料磨粉机刀盘直径最小为 400mm，最大为 800mm，属于涡轮式磨粉机系列。主要应用于硬质 PVC 回收领域，如 PVC 管材、型材、板材的次品及边角余料的回收。

The SMW series mute vertical turo-type plastic pulverizer belongs to the turbo-type pulverizer series, with its blade- disk diameter ranging from 400mm to 800mm. This kind of pulverizer is featured by high speed and is widely used in recycling hard PVC. For example, it can grind PVC pipe, PVC profile, and PVC sheet...

特点 Advantages

- 研磨间隙调节安全可靠
- 低能耗，高产量
- 设计创新高效
- 操作维护简便
- 配套设施齐全
- 自动回磨功能
- 风水双冷却系统

- Safe and convenient adjustment of cutting gap
- Low drive power and High throughput
- Innovative and energy efficient design
- Easy to maintain and control
- Wide range of accessories
- Regrinding coarse powder automatically
- Dual cooling system

主要技术参数 Main technical parameters

材料	Material	SMW-500	SMW-600	SMW-800
刀盘	Blades Disk	483±1	583±1	783±1
主电机功率	Main Motor (kw)	37	45	75
重量	Weight(kg)	1680	2080	2980
外型尺寸	Dimensions(mm)	3000×2800×3900	3200×3000×4200	4000×3500×4500
产量	Capacity(kg/h)	120-300	180-480	320-880

注：产量取决于磨粉材料的种类和磨粉细度，进料大小一般在5–8mm

Attention: the throughput depends on the types and size of grinding materials,along with the finess of the grinding materials.Usually, the original diameter of the material ranges from 5 to 8 mm.



SMW系列高速涡轮式塑料磨粉机

SMW SERIES HIGH SPEED TURBO-TYPE PLASTIC PULVERIZER

该款塑料磨粉机属于涡轮式磨粉机系列。主要应用于硬质 PVC 回收领域，如 PVC 管材、型材、板材的次品及边角余料的回收。

1. 与同类型磨粉机相比，在同功耗的情况下产量有较大提高（增产 20%–50%），节约能耗。
2. 增加了集尘装置，有效地降低了粉尘污染。
3. 关风机出料降低了操作工人的劳动强度。
4. 主机门盖可打开，便于检修和刀具的更换。
5. 采用风水双冷，较好降低了机体内的工作温度，所磨制的料不易变性，同时也有利于热敏性塑料的磨制，可对部分 PE、ABS 进行磨制。
6. 20–100 目可调且调节简便。

The machine is our latest self-developed grinding mill. It is mainly used in the fields of recycling of hard PVC. For instance, it can grind unqualified PVC pipes, PVC profile, PVC sheet and so on.

1.Compared with similar grinders, its output is greatly improved (increased by 20%-50%) under the same power. It is energy-saving.
2.The dust collector is added to reduce dust pollution effectively.
3.The discharging of the main fan reduces labors intensity of operating workers.
4.The door cover of the host can be opened for convenience of maintenance and replacement of cutters.
5.Wind and water cooling system are adopted to decrease the working temperature inside the machine body, which does good to keep the material characteristics. At the same time, it is conducive to grind heat sensitivity plastics like PE and ABS.
6.The powder mesh is adjustable (20-100 mesh).

主要技术参数 Main technical parameters

材料	Material	SMW-400	SMW-500	SMW-600	SMW-800
刀盘	Blades Disk	390±1	483±1	583±1	783±1
主电机功率	Main Motor (kw)	30	37	45	75
重量	Weight(kg)	1000	1280	1680	2180
外型尺寸	Dimensions(mm)	1250×1500×1530	5600×1500×2900	5900×1600×3200	6200×2000×3500
产量	Capacity(kg/h)	50-120	120-260	160-450	250-850

注：产量取决于磨粉材料的种类和磨粉细度，进料大小一般在5–8mm

Attention: the throughput depends on the types and size of grinding materials,along with the finess of the grinding materials.Usually, the original diameter of the material ranges from 5 to 8 mm.

SMW系列立式塑料磨粉机

SMW SERIES VERTICAL PLASTIC PULVERIZER

本厂吸收国外先进技术研制开发的系列磨粉机。主要应用于硬质 PVC 回收领域，如 PVC 管材、型材、板材的次品及边角余料的回收。

采用风水双冷可直接对物料、刀片、齿板冷却，而本机更是强风冷却，可显著降低机内温度，有利于热敏性塑料的研磨。

在刀盘高速旋转的气流中物料因离心力的作用被甩向齿板，在刀片与齿板间撞击摩擦而粉碎。细粉随气流排出，贴近齿板的粗粒料因挡板的阻碍不能排除被继续粉碎直至呈粉料随风排出。

20–100 目可调且调节简便。

The machine is our latest self-developed grinding mill. It is mainly used in the fields of recycling of hard PVC. For instance, it can grind unqualified PVC pipes, PVC profile, PVC sheet and so on.

Double cooling system (wind & water) can cool down the temperature of material, blade and tooth-shaped plate. This machine has applied strong wind cooling system, which can apparently reduce internal temperature of the machine. Obviously, it is good for grinding heat sensitive tooth shaped plate. Fine powder exits with the air flow, while the coarse powder does not exit until it is finely milled.

The powder mesh is adjustable (20-100 mesh).

主要技术参数 Main technical parameters

材料	Material	SMW-500	SMW-600	SMW-800
刀盘	Blades Disk	483±1	583±1	783±1
主电机功率	Main Motor (kw)	37	45	75
重量	Weight (kg)	1280	1680	2180
外型尺寸	Dimensions (mm)	1700×1500×2900	1800×1600×2900	2000×1800×3000
产量	Capacity (kg/h)	120-280	180-450	280-880

注：产量取决于磨粉材料的种类和磨粉细度，进料大小一般在5–8mm

Attention: the throughput depends on the types and size of grinding materials,along with the finess of the grinding materials.Usually, the original diameter of the material ranges from 5 to 8 mm.

深冷粉碎机
CRYOGENIC MILL

一、工作原理及特点

本产品整套低温磨粉机由料仓、机械粉碎机、引风机、旋风器、气流筛(用户订配)、真空自动上料(用户订配)、液氮罐(用户自配)等组成。

1. 工作原理

该低温磨粉机系统以液氮为冷源，被粉碎物料通过冷却在低温下实现脆化粉碎状态后，进入机械粉碎机腔内通过叶轮高速旋转，物料与叶片、齿盘、物料与物料之间的相互反复冲击、碰撞、剪切、摩擦等综合作用下，达到粉碎效果；被粉碎后的物料有气流筛分机进行分级并收集，没有达到细度要求的物料返回料仓继续粉碎，冷气大部分返回料仓循环使用。

2. 特点

该低温磨粉机系统在物料粉碎过程中，其冷源形成一个闭路循环系统，使能源得到充分利用，节省能耗；粉碎用的冷源温度可降至 -196 度，根据物料的脆化点温度，在粉碎过程中其温度可调节，选择最佳粉碎温度，降低能耗。粉碎细度可达到 10–700 目，甚至达到微米等细度。使用液氮作为研磨介质，实现超低温粉碎，物料的防爆、防氧化等综合效果。

二、使用范围

该低温磨粉机系统使用于在常温下无法粉碎的各种物料，广泛应用于各种化工、石化、机械、船舶、汽车行业、电子行业、服装、涂料、印刷、工程塑料、橡胶、鞋材、热塑性物料、热熔胶、尼龙、聚酯、聚丙烯、聚乙烯、热塑性弹性体 TPU、TPEE、尼龙类 PA11、PA1010、PA12、PA6、PA66、PA610 共聚尼龙、聚酯类、聚四氟乙烯、EVA、食品行业（辣椒粉）、中西药材等等产品的超细粉碎。

三、低温磨粉机全套设备工艺流程配置

液氮罐、料仓、机械粉碎机、引风机、旋风下料器

深冷粉碎机——低温粉碎机：该设备以液氮为冷冻剂，将被粉碎的物料降至玻璃化温度，利用物质在低温下变脆的性质。在高速冲击和摩擦下使物质粉碎。粉碎后的产品具有不变质，不氧化，粒度分布均匀，几何图形好的特点。该技术广泛应用于食品行业、医药行业、塑料行业、化工行业、科学研究、航天航空等领域。

主要技术参数 Main technical parameters

粉碎机工作室直径	Diameter of fragments room	Φ423mm
粉碎机功率	Main motor power	45kw
总功率	Total power	60kw
冷媒	Medium	液氮 Liquid nitrogen
工作温度	Temperature	0℃ — -196℃(可调控 adjustable)
粉碎细度	Fineness	10-700 目mesh
外形尺寸	Dimension	4000*2000*2200(高)mm
机器总重	Weight	3000kg
产量	Capacity	100-1000kg/h (根据物料 depend on materials)
整个系统全变频器控制	Frequency conversion control is used in the whole system.	

The full set of deep cold pulverizer is composed of feeding bin, mechanical pulverizer, induced draft fan, cyclone, vibration sieve, liquid nitrogen tanks and other components.

(1) Working principle

This deep cold pulverizer system takes liquid nitrogen as cold source and use the brittleness of the stuffs under cold temperature. When the cold brittle stuffs enter into the pulverizer chamber, with high speed revolution of impellers, the stuffs inside will be pulverized through the integrated effects of mutual repeat impact, collision, shearing, rubbing between stuffs and stuffs, stuffs and vane, stuffs and gear plate. The stuffs after pulverization will be classified and collected. The particles which haven't reached the size requirement will be returned back to the bin and pulverized again, most of the cooling air will be also recycled.

(2) Features

In the process of pulverizing, the cold source comes into being a closed loop system, which makes full use of energy and save the engery. The cold medium temperature can be reached upto -196 degree Celsius. It can be adjusted according to the brittleness point of different stuffs. The pulverizing powder granule ranges from 50-400 mesh. Using liquid nitrogen as medium achieves ultra-low temperature pulverizing to avoid the explosion and oxidation and so on.

(3)Range of application

The low temperature grinding machine system can grind various materials which can't be shattered in room temperature, and is widely used in all kinds of chemical, petrochemical, machinery, ship, automobile industry, electronic industry, clothing, coatings, printing, engineering plastic, rubber, shoes, thermoplastic materials, hot melt adhesive, nylon, polyester, polypropylene and polyethylene, thermoplastic elastomer TPU, TPEE, nylon PA11, of PA1010, PA12, PA6, PA66, PA610 copolymerization of nylon, polyester, Polytetrafluoroethylene, EVA, food industry (chili powder), Chinese and western medicine and so on.

PC系列塑料破碎机

PC SERIES CRUSHER

PC 系列破碎机广泛用于管材、机头料、板材、PET 瓶的回收再利用。

PC 系列破碎机有如下特点：

1. 钢结构箱体，铸钢刀具，夹钢刀具，避免崩裂；
2. 阶梯式刀具，提高剪切力，增加破碎效率；
3. 活动式筛网，拆装方便，便于清洗换色；
4. 入料门设隔音夹层，降低噪音，改善环境；
5. 机脚附加滑轮，移动方便；
6. 与撕碎机配套使用可提高破碎效率。

PC series Crusher is used for crushing pipes, first-coming extrusion materialsplates and PET bottles.

We can design it with dry/wet crushing.

It has the following characteristics:

1. Steel structure tank, cast steel knife rest, holder steel cutters, avoiding crack;
2. Ladder style cutters, improving the shear force, improve crushing efficiency;
3. Movable screen, dismounting convenience, easy for cleaning and color change;
4. Sound insulation interface is used in the feeding hopper to reduce the noise and improve the environment;
5.Foot-wheel mechanism makes it more easily;
6. A protective switch is put in the feeding hopper to protect the operator's safety.

SWP系列塑料破碎机

SWP SERIES CRUSHER

特点及用途

SWP 系列卧式塑料破碎机主要适用于破碎较长的 PVC 异型材和管材，如：塑料门窗、塑料管、板材等，不需切割分段，可一次性连续投料。SWP 系列塑料破碎机内部独特设计，是专门为破碎较硬与韧性塑料型材而设计的新型破碎机，是在 SPW 系列破碎机的基础上做的改进和延伸。该机型可实现自动进料，并设有风机输送碎料装置、开启装置、操作与维修极为方便，是破碎各种管材和异型材的理想机型。

SWP Series Horizontal Plastic Breaking Machine is mainly used for breaking relatively long PVC special shaped material, such as plastic door & window, plastic pipe, sheet, etc. There is no need to cut. Once continuous feeding can be conducted. Internal design of SWP Series Horizontal Plastic Breaking Machine is rather distinct. It is a new kind of breaking machine used for breaking plastic profiled material with large hardness and tenacity. It is improved and extended on the basis of SPW series breaking machine. Automatic feeding can be realized for this model. Fan blower is arranged for transport of broken material, start-up device is arranged. The operation and maintenance & repair is rather simple. It is an ideal model for breaking all sorts of pipe material and profiled material.

单轴撕碎机

SS SERIES SHREDDER

单轴撕碎机是我公司专门针对破碎成卷或打包后的薄膜、挤出机机头料、大型硬块料及分切后的管类而研制的新型撕碎机。作为国内生产塑料机械的骨干企业，有多年单轴撕碎机的生产经验和在自身技术基础上引进吸收国内外先进技术，同时积极吸取客户使用机器的工作经验和好的建议，在生产技术和研发上作出不断的努力，产品销往国内外，受到很多客户的青睐与好评。

单轴撕碎机设备主要特点：

1. 单轴撕碎机转子上的刀座和刀片可拆卸，便于清洁、维护、保养；
2. 单轴撕碎机每把动刀有 4 个切削刃，磨损后可旋转 90° 继续使用；
3. 单轴撕碎机主轴由齿轮减速箱驱动，运行平稳，噪音低，扭矩大；
4. 单轴撕碎机采用 PLC 程序控制系统，可自动正反转，使机器运行更安全可靠；
5. 单轴撕碎机的箱体采用焊接，焊后回火处理，消除了焊接应力；
6. 单轴撕碎机动刀安装位置采用加工中心精密加工，确保每一个动刀与定刀的间隙相同；
7. 单轴撕碎机动刀座采用嵌入式方式用高强度螺钉连接在刀轴上，可有效防止焊接式在长期震动后产生的掉刀现象；

该系列单轴破碎机包括：SS/F600、SS/F800、SS/F1000、SS/F1200、SS/F1400。

The single-Shaft Shredders with SS/F600 type are newly-designed especially for crushing the film in rolls or in bales, first-coming extrusion materials, large and hard blocks and lumps, pipes after cutting and so on. The shredders have the characteristics of strong crushing ability and contrarotation with the structure of close-lined rotary knives in single direction. The motor can be protected effectively with the contrarotation characteristic.

Features of Single-shaft shredder:

1.Movable blade,dismounting convenience, easy for cleaning and maintenance.
2.Each rotary blade has four cutting edge and can be used again after rotating 90°.
3.Having gear reducer with spindle，smooth operation, low noise, large rotating torque.
4.PLC control system，processing in two different directions automatically，running machine more safety.
5. Backfire treament after weldinging tank，dissolve weld stress.
6.Blade position apply precision machining，making sure the same space between each rotary knife and fixed knife.
7.Rotary blade position adopts embedded with high-strength screw connected to blade spindle, can prevent the phenomenon that welding blade drop by long-term vibration.

大型撕碎机 Big Shredder

平行撕碎机 Level Shredder

斜式撕碎机 Inclined Shredder

双电机撕碎机 Double Motor Single-shaft Shredder

SRL-W系列卧式混合机组

SRL-W SERIES HORIZONTAL TYPE MIXER

设备特点 Characteristics of the equipment:

1、用于各种塑料的配料、混合、干燥、着色等工艺，是型材、管材生产厂家最理想的首选设备。
2、主轴密封装置具有电、汽两种加热功能。
3、锅盖采用双道密封，热混锅盖的开启采用气动，冷混锅盖开启采用气动或手动。
4、电气控制采用进口名牌仪表及控制元件，实现自动控制。
5、选配有脉冲除尘回收装置。
6、浆叶均通过静、动平衡试验机特殊试验。
7、另可选配简易上料系统。

1. Applied to all kinds of plastic technics such as mixture、mixing、drying、coloring, preferences by pipe manufacturers.
2. Shaft seal device with two functions of electrical heating and steam heating.
3. The cover adopt double sealing, hot compounding cover with pneumatic start, and cooling compounding cover with pneumatic start or manual start.
4. Imported famous meter and control elements equipped on electrical control cabinet to achieve automation.
5. Matching pulse dust collector.
6. Blade has got through special test with static-dynamic balancing test.
7. Simple feeding system is available.

SRL-Z系列立式混合机组

SRL-Z SERIES VERTICAL TYPE MIXER

主要技术参数 Main technical parameters

型号	Model	SRL-Z100/200A	SRL-Z200/500A	SRL-Z300/600A	SRL-Z300/1000A	SRL-Z500/1000A	SRL-Z500-1600B	SRL-Z800-2000B	SRL-Z1000-2500B
总容积	Capacity(L)	100/200	200/500	300/600	300/1000	500/1000	500/1600	800/2000	1000/2500
有效容积	Effective Capacity(L)	75/160	150/320	200/360	200/640	375/640	375/1200	600/1280	750/2000
浆叶转速	Paddle(rpm)	650/1300/180	475/950/130	475/950/130	475/950/110	430/260/50	430/860/50	370/740/50	370/740/50
电机及加热功率	Motor & Heating Power(kw)	14/22/7.5/6	30/42/11/9	40/55/11/9	40/55/15/9	47/67/15/12	55/75/18.5/12	83/110/30/15	110/160/30/20
耗水量	WaterConsumption m³/(min)	3.5	5	5.8	6.7	7.8	12	14	17
耗气量	GasesConsumption m³/(min)	0.3	0.4	0.4	0.4	0.4	0.45	0.45	0.5
加热方式	Heating Method	电加热及自摩擦	电加热及自摩擦	电加热及自摩擦	电加热及自摩擦	电加热及自摩擦	电加热及自摩擦	电加热及自摩擦	电加热及自摩擦
卸料方式	Discharge Method	手动/气动	手动/气动	手动/气动	手动/气动	手动/气动	手动/气动	手动/气动	手动/气动
外形尺寸	Outlook Size(mm)	3780/1870/2250	4850/2240/2470	4680/2240/2740	4980/2500/2740	5580/2700/3432	4680/3000/4120	5260/3200/4378	6540/3460/4400
重量	Weight (T)	3.2	3.5	3.8	4.2	5.8	8.5	9.5	12
混合时间(分/锅) Mixing Time m/p.pot	热Heat	6-10	6-10	6-10	6-10	6-10	6-10	10	10
	冷Cool	8-10	8-10	8-10	8-10	8-10	8-10	12	12

PE管材生产线
PE PIPE PRODUCTION LINE

UPVC双管挤出生产线
UPVC DOUBLE-PIPE EXTRUSION LINE

PVC型材生产线

PVC PROFILES EXTRUSION LINE

宽幅门板生产线

PVC PLASTIC WOOD DOOR PANEL EXTRUDING PRODUCTION LINE



PE、PP薄膜破碎清洗线

PE，PP FILM CLEANING LINE

PE 薄膜破碎清洗线从开始作业到成品，可非常容易的清洗废塑料制品、薄膜制品。废脏农用薄膜，废包装材料或硬塑料在这里一步步得到处理。整条生产线简洁而有效的设计使得流水线在国内外大受欢迎。严格按照 CE 认证要求的生产工艺使得机器的质量，安全性更加的可靠。

Our PE PP film washing and recycling machine could deal with waste plastic such as plastic bags,agriculture film,plastic package products and so on. The design of whole line is concise and popular all over the world,besides,our products are surely of standard and high quality with CE certification and ISO 9001,we are looking forward to cooperating with you!

PET瓶片回收清洗设备(600-2000kg/h)

PET BOTTLE FLAKES RECYCLING, WASHING & CLEANING EQUIPMENT



辅助机械 AUXILIARY MACHINERY

混合着色机 Mixer coloer Machinery

KFJ系列真空粉末加料机
KFJ Series Vacuum Power Charger

SML系列模具冷却器
SML Series Mould Cooler

YJ系列油加热
YJ Series Oil Heater

MK系列模具温度控制器
MK Series Mould Temperature Controller

ZJ系列塑料自动加料机
ZJ Series Plastics Automactic Charger

KFJ系列真空粉末加料机
KFJ Series Vacuum Power Charger

STG-U系列料斗式塑料干燥机
STG-U Series hopper plastic dryer

CSG除湿式干燥机
CSG Dehumidification & dryer

真空定型箱 Vacuum Calibration Tank

振动筛 Vibrosieve

CJ磁力架
CJ Series Magnetic Force Frame

收卷机系列 Winder Series

我们的服务 OUR SERVICE

售前服务–公司内部培训
Service before sale---training within the company

量体裁衣：根据客户的真正需求精心设计，最大可能地实现客户的需求，为客户提供最完善、最经济、最适用的解决方案。

Customer-oriented: best-developed, the most economic and the most suitable solution will be carefully designed to meet the customers' taste and needs.

HUIBANG MACHINERY

售中服务–与客户沟通
Service in sale---communication with customers

精心准备：从市场调研、技术交流到技术培训和技术辅导，与客户深入沟通，相互了解，彻底地理解客户的使用要求。

Careful preparation: deeper communication with and fuller understanding of the customers and their needs will be achieved in such ways: market survey; technique exchange, training and consultancy.

售后服务–检修和维护产品
Service after sale---inspection and maintenance

我们的售后服务目标：竭尽我们所能；确保用户满意。
我们的售后服务宗旨：做好售后服务，不惜百倍代价。
我们的售后服务宣言：诚信为先、用户至上、全新服务、超值享用；我们始终尊重客户对我们的选择，我们致力于为客户提供物超所值的产品和服务，以"客户满意度"作为服务的唯一标准，赢得客户的长期信赖。

Our after-sale service objective: trying our best and ensuring their satisfaction

Our after-sale service aim: achieving the best result at all costs

Our after-sale service manifesto: being honest, respecting the customers, new service, highly economic

We always respect the customers' choices. We devote ourselves to providing satisfactory products and service at low costs, taking the extent of the customers' satisfaction as the sole standard, and so we have earned their long-term trust.

惠邦服务中心 24 小时服务联系方式

联系电话(TEL)：+86-512-58964890　+86-512-58639891
传　真(FAX)：+86-512-58964836
邮　箱(E-MAIL)：webmaster@hb1888.com